





Outdoor IR IP Camera, H.264, with Optical Smart Zoom & Vari-focal Lens

Feature:


- 1/3" H.R. CCD image sensor
- Resolution: NTSC: 768(H) x 494(V), PAL: 752(H) x 582(V)
- MPEG4, MJPEG and H.264 compression
- Smart Zoom: zoom in on the object that triggered the alarm
- True Day & Night surveillance with IR shifter & large aperture lens (F1.8)
- Vari-focal Lens f4.0mm \sim f9.0mm, View: 75° \sim 36°
- Outdoor IP Rating with IP67
- Longer IR effective distance up to 40 meters
- High resolution with the best video performance
- Smart Light Control to avoid overexposure
- Excellent outdoor ID design with cable management
- Durable 56 IR LEDs built-in application
- Motion detection and alarm notification via Email
- Supports 3G Mobile Phone Surveillance (iPhone, BlackBerry, WinCE, J2ME & Android, Symbian Support)
- Supports multiple access levels with password
- Supports up to 10 users on-line
- Complete IP surveillance system with Central Management System (CMS) software for up to 16 cameras at the same time

Specification:

 Environment 	
In/Out door use	Outdoor
Day/Night	Yes
 Network 	
LAN Port	YES
LAN Port LAN Connection	YES 10/100 Based-T Ethernet

Remark: For 3G Mobile Phone Surveillance, please download the mobile software installation for remote Surveillance via Mobile Phone or PDA from www.logilink.com.












Outdoor IR IP Camera, H.264, with Optical Smart Zoom & Vari-focal Lens

Specification:

Specification:		
Number of Online Users	10	
Network	With 3G Mobile Phone Surveillance	
• Video		
Video Compression	H.264 / MPEG4 / MJPEG	
Video Remote Control	YES	
Video Adjustment	Brightness, Contrast, Saturation and Hue	
Camera		
Image Sensor	1/3" HR color CCD image sensor	
Pixels	NTSC: 768(H) x 494(V) / PAL: 752(H) x 582(V))	
Min Illumination	0.05 Lux / F1.4, 0 Lux (IR ON)	
Shutter Speed	1/60 (1/50) to 1/100,000 sec.	
Lens	2.25x Zoom F1.8/f4.0mm~f9.0mm	
Viewing Angle	75° ~ 36°	
IR LED	56 units	
IR Effective Range	Up to 40 meters	
IR Shift	YES	
Smart Light Control	YES	
Smart Zoom	YES	
Auto Tracking	YES	
BLC	On/Off	
White Balance	ATW	
AGC	Auto	
IRIS Mode	Al / AES	
IP Rating	IP67	





^{*} The specifications are subject to change without notice.

^{**} Dimensional tolerance: (± 5mm)







Outdoor IR IP Camera, H.264, with Optical Smart Zoom & Vari-focal Lens

Specification:

Software	
Supported Protocols	DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP, HTTP, RTSP
Security	Multiple user access levels with password protection
Web Management	The licensed software "Video Viewer" for up to 16 network cameras control simultaneously
Remote Control	YES
Motion Detection	YES
Alarm and event Notification	Image upload over FTP and Email
Mobile	Supports 3GPP mobile surveillance
Others	
Power Source (±10%)	AC100V ~ 240V
Operating Temp.	-20°C~40°C
Minimum Web Browsing	- Pentium 4 CPU 1.3 GHz or higher, or equivalent AMD - 256 MB RAM
Requirements:	- AGP graphics card, Direct Draw, 32MB RAM - Windows 7, Vista, XP, Windows 2000 Server, ME, 98, DirectX 9.0 or later - Internet Explorer 6.x or later
Dimensions (mm)**	282.4(L) x 117.89(W) x 212.63(H)





* The specifications and pictures are subject to change without notice. *All trade names referenced are the registered namework of their respective owners.







Outdoor IR IP Camera, H.264, with Optical Smart Zoom & Vari-focal Lens

Package contents

- 1 x Outdoor IR IP Camera
- 1 x RJ45 Coupler
- 1 x Bracket
- 1 x CD-ROM disc for user manual & licensed software "Video Viewer" Optional: Power Adapter DC12 1.5A

Packaging Information:

• Packing Dimension: 405x164x246 mm

• Packing Weight: 2.3kg

• Carton Dimension: 428x355x522 mm

Carton Q'ty: 4pcs

• Carton Weight: 9.46kgs





