



Art No. CV0043

## Mini DisplayPort + Toslink Audio to HDMI Adapter

Mini DisplayPort of MacBook can only transmit video signal but no audio. However, this unique designed Adapter solved this trouble for users. It integrates Mini DisplayPort video signal and digital audio signal from MacBook into HDMI output. To connect the digital audio through stereo port, a piece of special fiber cable is provided by us. It allows users to enjoy perfect image and sound on HDTV.

### Feature:

- Supports Mini DisplayPort 1.1a input, USB 2.0 input and HDMI High Speed output
- Works by integrating mini DisplayPort video source and digital audio source of the MacBook into HDMI output
- Supplied a piece of special fiber cable
- Powered from Mini DisplayPort and USB Port
- Supports HDMI 225MHz/2.25Gbps per channel (6.75 Gbps all channel) bandwidth.
- Supports HDMI resolution of max up to 1080p
- Supports HDMI 12bit per channel (36bit all channel) deep color
- Supports uncompressed audio such as LPCM

### Package Contents:

- 1 x Main Unit
- 1 x Special Fiber Cable

### Packaging Information:

- Packing Dimension: 162x230x2 mm
- Packing Weight: 0.12kg
- Carton Dimension: 570x420x260 mm
- Carton Q'ty: 90pcs
- Carton Weight: 12.5kgs





Art No. CV0043

## Mini DisplayPort + Toslink Audio to HDMI Adapter

### Specification:

Signal Inputs/Output	
Input Video Signal	Mini DisplayPort
Input Audio Signal	SPDIF Audio
Output Video	HDMI High Speed
Input/Output Connector	Input: Mini DisplayPort Male 20pin USB 2.0 A type Male Special Fiber Connector Output: HDMI Female Type A 19pin
Operating Frequency	
Vertical Frequency Range	50/60Hz
Video Amplifier Bandwidth	2.25Gbps/225MHz
Resolutions(HDTV)	480p, 720p, 1080i, 1080p
Environmental	
Operating Temperature	0°C to +70°C
Operating Humidity	10% to 85 % RH (no condensation)
Storage Temperature	-10°C to +80°C
Storage Humidity	5% to 90 % RH (no condensation)
Power Requirement	
External Power Supply	No external power needed
Power consumption (Max)	2W

