



Art No. NS0056

24-Port Fast Ethernet POE Switch, Web Smart, 19"

NS0056 is 24-port 10/100M with PoE + 2 Combo Gigabit Copper / 2 SFP Rackmount Gigabit Web Smart Ethernet Switch that is designed for medium or large network environment to strengthen its network connection. Including Rackmount brackets, the 19" size fits into your rack environment. It is a superb choice to boost your network with better performance and efficiency.

IEEE 802.3af Power over Ethernet (PoE) ports

NS0056 features IEEE 802.3af Power over Ethernet (PoE) ports supplying Maximum 390 Watt. This product can convert standard 100~240V/AC power into low-voltage DC that runs over existing LAN cable to power up IEEE 802.3af compliant network accessories. It also features PoE awareness to verify whether the network device receive power is IEEE 802.3af compliant, or only the data will be sent through LAN cable. By adding NS0056 to existing networking, installing networking products such as Access Points and IP cameras can be easily managed and set up. Wireless device deployments are easily located with available power outlets and network administrators don't need to use heavy AC power adapters anymore.

2 Combo Gigabit Copper / 2 SFP Open Slots

NS0056 supports 2 Combo Gigabit Copper or 2 SFP open slots to uplink to servers, storage, or other switching devices for long loop reach applications

Exceptionally Smart

NS0056 provides Smart features that are ideal for simple QoS/CoS applications and basic monitoring tools to improve network efficiency. Its security and management features such as bandwidth control and VLANs to secure your network. Through a Web-based interface, an administrator can set up VLANs to segregate traffic, QoS to prioritize mission-critical data and link aggregation to create fat traffic pipelines. All of these features offer extra protection on the network edge. Best of all, the password-protected configuration interface can be accessed remotely.

Auto-MDI/MDI-X

Every port can automatically sense your type of cable, so there is no need for crossover cables whether you are connecting this switch to another switch or to a computer.



Art No. NS0056

24-Port Fast Ethernet POE Switch, Web Smart, 19"

Auto-Negotiation

Every port can automatically sense if the connected network devices are running at 10Mbps, 100Mbps, or 1000Mbps and Half/Full-Duplex mode, and adjust accordingly.

Non-Blocking

This switch receives and forwards traffic seamlessly with its non-blocking wire-speed. Every port simultaneously supports up to 200 or 2000Mbps of bandwidth in full-duplex mode. This feature provides full wire speed to the connected devices and allows you to run a smooth network.

Store and Forward

By this function, this switch can maximize network performance while minimizing the propagation of bad network packets.

Features:

- 24-Port 10/100BaseT(X) with PoE + 2-Port Gigabit Copper and 2 SFP Open Slots
- Web-based Configuration and Management
- 19" Industrial Size
- Internal Power Supply

Technical Specifications

Standards	IEEE 802.3 10BaseT IEEE 802.3u 100BaseTX IEEE 802.ab 1000BaseT IEEE 802.3z 1000BaseSX/LX IEEE 802.3x Full-duplex and Flow Control IEEE 802.1Q VLAN IEEE 802.1p QoS / Class of Service, Priority Protocols IEEE802.3 Nway Auto-negotiation IEEE802.3af Power over Ethernet IEEE 802.1w Rapid Spanning Tree Protocol
-----------	---



Art No. NS0056

24-Port Fast Ethernet POE Switch, Web Smart, 19"

Technical Specifications

Features	Number of Ports: 10/100BaseTX with RJ-45 Connectors: 24 port with PoE 10/100/1000BaseT with RJ-45 Connectors: 2
	Combo SFP Open Slots: 2 MAC Address: 4K Buffer Memory: 2.75Mb Transmission Method: Store and Forward
Smart Features	Port Security Filter: TCP / UDP port based, MAC Address based, IP Address based VLAN Setting: Tag Based: 32 ; Port Based: 26 VLAN ID (Up to 4094 K) QoS: Priority (Port Based / TOS / Diffserv / DSCP/IPv4 /IPv6) Class of Service Configuration TCP / UDP Port Based Management: Password-protected Access, On / Off PoE Port Settings Web-Based Management Graphic User Interface Bandwidth Control Broadcast Storm Control Port Mirroring Port Configuration Programmable aging timer IGMP Snooping Trunk (up to 4 Ports per Group, 2 Groups per Device) Provide DHCP Client Quality of Service: up to 2 queues



Art No. NS0056

24-Port Fast Ethernet POE Switch, Web Smart, 19"

Technical Specifications

Filtering/Forwarding Rates	1000Mbps port – 1,488,000pps ; 100Mbps port - 148,800pps ; 10Mbps port - 14,880pps
Transmission Media	10/100BaseTX Cat. 5 UTP/STP ; 1000BaseT Cat. 5 / Cat. 5E UTP/STP
Led Indicators	Per Port: Link/Act, PoE : Act / Status, Per Unit: Power
Power Input	100~240V/AC, 50~60Hz
Power Output	48V/DC Per Port Output
Power Consumption	390 Watts (Max.)
Dimensions	440x332x44 mm (L x W x H)
Operating Temperature	0 to 55°C
Storage Temperature	-20 to 90°C
Humidity	10 to 90% RH (non-condensing)
Certifications	FCC Class A, CE

Package Contents:

- 1 x 24-Port Fast Ethernet POE Switch, Web Smart, 19"
- 1 x Power Adapter
- 1 x User Manual

Packaging Information:

- Packing Dimension: mm
- Packing Weight: kg
- Carton Dimension: mm
- Carton Q'ty: pcs
- Carton Weight: kgs

